



Kodak  
Authorized  
Reseller  
www.fotoclubinc.com



# KODAK

## KODAK PROFESSIONAL Inkjet Photo Paper, Lustre / 255g – Dry Lab

Featuring a true photographic resin-coated base paper and e-surface finish with “pulp of unsurpassed quality,” KODAK PROFESSIONAL Inkjet Photo Paper gives you the freedom to print in your studio, and the KODAK PROFESSIONAL back-print seal of quality to back it up. KODAK PROFESSIONAL Inkjet Photo Paper is compatible with Noritsu, Fuji and Epson Dry Lab printers.

Size	Quantity	SKU
4" x 328'	4-pack	KPR04LDL
5" x 328'	4-pack	KPR05LDL
6" x 328'	4-pack	KPR06LDL
8" x 328'	2-pack	KPR08LDL
10" x 328'	2-pack	KPR010LDL
12" x 328'	2-pack	KPR012LDL



©Brand Management Group, 2013  
The Kodak and Kodak Professional trademarks and Kodak trade dress are used under license from Kodak.

### FEATURES:

- 10-mil, 255-gram e-surface photo paper
- Microporous, instant-dry coating on a resin-coated paper base
- Kodak Watermark on back of Photo Paper
- Compatible with Noritsu, Fuji and Epson Dry Lab printers
- Bright white point provides clean highlight detail
- Thermal and cold laminate compatible

### APPLICATIONS:

- High-end photographs
- Fine art reproductions
- Photo albums, greeting cards, photo books and other Dry Lab applications

# Kodak PROFESSIONAL Inkjet Photo Paper, Lustre / 255g - Dry Lab

Featuring a true photographic resin-coated base paper and e-surface finish with “pulp of unsurpassed quality,” KODAK PROFESSIONAL Inkjet Photo Paper gives you the freedom to print in your studio, and the KODAK PROFESSIONAL back-print seal of quality to back it up. KODAK PROFESSIONAL Inkjet Photo Paper is compatible with Noritsu, Fuji and Epson Dry Lab printers.

Property	Specifications
Material	Resin-coated photo base
Gauge	10 mil / 255g
Gloss Level	>/=25
Opacity	>90%
Whiteness	>134
Printer/Ink Compatibility	Compatible with Noritsu, Fuji and Epson Dry Lab printers.
Light-fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Finishing/Post Processing	It is always recommended that a protective laminate be applied after printing. Hand applying laminate is not recommended. Pressure-sensitive or thermal laminates can be used. Before applying the laminate, allow the image to dry for 24 hours.
Optimal Service Environment	72° F (21° C), 50% R.H For end use: 0-300° F
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the BMG ship date when stored in proper conditions.

**Product Performance & Suitability:** All of the descriptive information and recommendations for the use of Kodak products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by BMG. All Purchasers of Kodak products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor the manufacturer shall be liable either in the tort in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect in agreement signed by officers of seller and manufacturer.